



G Thread	dimensions		B1	Lock nut Appropriate bearing(s) (kg)		
	d	d1		Lock nut	Appropriate bearing(s) (kg)	
M115x2	110	105	82	KM23	24122K30	0.71
M130x2	120	115	93	KM26	24124K30	1
M140x2	130	125	94	KM28	24126K30	1.15
M150x2	140	135	99	KM30	24128K30	1.3
M160x3	150	145	115	KM32	24130K30	1.55
M170x3	160	150	124	KM34	24132K30	3
M180x3	170	160	125	KM36	24134K30	3.25
M190x3	180	170	134	KM38	24136K30	3.75
M200x3	190	180	146	KM40	24138K30	4.45
Tr210x4	200	190	158	HM42	24140K30	5.05
Tr230x4	220	200	170	HM46	24144K30	10
Tr260x4	240	220	180	HM52	24148K30	11.5
Tr280x4	260	240	202	HM56	24152K30	14
Tr300x4	280	260	202	HM60	24156K30	15
Tr320x5	300	280	224	HM64	24160K30	18.5
Tr340x5	320	300	242	HM68	24164K30	20.5
Tr360x5	340	320	269	HM72	24168K30	25.5
Tr380x5	360	340	269	HM76	24172K30	26
Tr400x5	380	360	271	HM80	24176K30	31
Tr420x5	400	380	278	HM84	24180K30	35
Tr440x5	420	400	310	HM88	24184K30	39
Tr460x5	440	420	310	HM92	24188K30	45.5
Tr480x5	460	440	332	HM96	24192K30	50

AH241 SERIES

Tr500x5	480	460	340	HM/500	24196K30	51.5
Tr530x6	500	480	360	HM/530	241/500K30	57
Tr560x6	530	500	370	HM/560	241/530K30	91.5
Tr600x6	560	530	393	HM/600	241/560K30	107
Tr630x6	600	570	413	HM/630	241/600K30	118
Tr670x6	630	600	440	HM/670	241/630K30	136
Tr710x7	670	630	452	HM/710	241/670K30	185